

CORSO LED N SE

Stropní LED svítidlo



 [V] 220-240 AC	 [Hz] 50	 [°] 120	 [h] ≥10000	 [h] 20000	 ellipse ≤ 60 Macadam	 Ra 80
 SMD		 IP 44	 -20+35	 [°C] -20+35		
 0,75-2,5	 [mm²] max 8	 [m] H360	 [s] - [min] 5-10	 micro wave	 25-2000	
 0,5m						



	 [W]	 [lm]	 Tc [K]	
CORSO LED N 12-NW-SE 31099	12	800	4000	bílá
CORSO LED N 18-NW-SE 31100	18	1200	4000	bílá
CORSO LED N 24-NW-SE 31101	24	1600	4000	bílá

CORSO N LED jsou plafony vybavené integrovaným světelným zdrojem LED SMD. Plafony s označením SE jsou navíc vybaveny mikrovlnným senzorem pohybu. Tato svítidla mají stupeň krytí IP 44, což umožňuje montáž uvnitř i zvenku budovy.

- Materiál korpusu: plast
- Materiál difuzoru: PMMA



CORSO LED N 12-NW-SE




CORSO LED N 18-NW-SE




CORSO LED N 24-NW-SE

CORSO LED N SE


Stropní LED svítidlo



CORSO LED N 12-NW-SE



CORSO LED N 18-NW-SE



CORSO LED N 24-NW-SE