

KRD10-4

Proudový chránič, 4P



[Hz]

50

°C

-25÷40

IP

20

0000

4P

0

4

TH 35

Ui [V]

400

(mm²)

max 25

CE

EAC

UK

CA

⬇

KRD10-4/25/30-F

	[V]	In [A]	Ian [mA]	Typ proudového chrániče	
KRD10-4/25/30-F	45776	400 AC	25	30	F 4
KRD10-4/32/30-F	45777	400 AC	32	30	F 4
KRD10-4/40/30-F	45778	400 AC	40	30	F 4
KRD10-4/63/30-F	45779	400 AC	63	30	F 4
KRD10-4/32/100-F	45780	400 AC	32	100	F 4
KRD10-4/63/100-F	45781	400 AC	63	100	F 4
KRD10-4/40/300-F	45782	400 AC	40	300	F 4
KRD10-4/63/300-F	45783	400 AC	63	300	F 4

Proudový chránič typu F je modernější verze, navržená pro instalace s elektronikou a jednofázovými měniči. Typ F reaguje na více druhů reziduálního proudu než klasický typ AC nebo A:

AC – střídavý sinusový proud

A – AC + pulzující DC

F – vše výše uvedené + proudy se smíšenými frekvencemi (do cca 1 kHz) a krátkodobé DC složky do 10 mA.

KRD10-4

Proudový chránič, 4P



KRD10-4/25/30-F



KRD10-4/32/30-F



KRD10-4/40/30-F



KRD10-4/63/30-F



KRD10-4/32/100-F



KRD10-4/63/100-F



KRD10-4/40/300-F



KRD10-4/63/300-F

