

ADLS-240 series

240W Enclosed Type Switching Power Supply



■ Features:

- Constant voltage design
- European AC input
- Protections: Short circuit / Overload / Over voltage /Over Temperature
- Cooling by free air convection
- Compact size
- Low price



5 9 0 2 1 3 5 1 1 9 4 4 0



ELECTRICAL SPECIFICATION

MODEL	ADLS-240-12
OUTPUT	
Rated Voltage	12V
Rated Current	20A
Rated Power	240W
Line Regulation	± 1%
Load Regulation	± 2%
Tolerance [3]	± 5%
Ripple & Noise (max.) [2]	1V _{p-p}
Setup, Rise Time [4]	500ms, 30ms / 230VAC at full load
Hold up Time	20ms / 230VAC at full load
INPUT	
Voltage Range	180 ÷ 264VAC
Frequency Range	47 ÷ 63Hz
Efficiency (typ.)	85%
AC Current (typ.)	2.5A / 230VAC
PROTECTIONS	
Overload	Range: 110 ÷ 170% rated current
	Type: fold forward mode(voltage rises, current drops), auto-recovery
Over voltage	13.5 ÷ 20.5V
	Type: hiccup mode, auto-recovery.
Over Temperature	Range: 110°C ± 10°C (detect by main IC)
	Type: shut-off, auto-recovery.

ADLS-240 series

240W Enclosed Type Switching Power Supply



WORKING ENVIRONMENT

Working Temperature	-20°C ÷ 50°C (Refer to Derating Curve)
Working Humidity	20 ÷ 90% RH non-condensing
Storage Temperature and Humidity	-40°C ÷ 80°C, 10 ÷ 95% RH non-condensing

SAFETY AND EMC REGULATIONS


Safety Standards	Compliance to EN61347-1, EN61347-2-13
Withstand Voltage	I-P/O-P: 1.5kVAC; I-P/GND: 1.5kVAC; O-P/GND: 0.5kVAC
EMC Emission	Compliance to EN55015
EMC Immunity	Compliance to EN61547
Harmonic Current	Compliance to EN61000-3-3; EN61000-3-2

OTHERS

Lifetime	12 000Hrs for input 230VAC, 20°C ambient temperature, full load
Dimensions	223 x 71.5 x 36mm (L x W x H)
Weight and Packing	0.54kg; 40pcs./ctn; ctn weight and dimensions: 24.5kg; 46 x 39.3 x 27cm

1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature.
2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1µF i 47µF parallel capacitor.
3. Tolerance includes set up tolerance, line regulation and load regulation.
4. Setup and rise time is measured from 0 to 90% rated output voltage.
5. Power supply is considered as component not indented to apply by end-user. Power supply meets safety and EMC standards however the final equipment with power supply must be re-quality to comply with EMC Directives.

MECHANICAL SPECIFICATION



TERMINAL PIN NO. ASSIGNMENT

PIN No.	Assignment	PIN No.	Assignment
1	Frame Ground: GND	4,6	Output: -V
2	Input: AC/L	7,8	Output: +V
3	Input: AC/N	LED1	Power On indicator

DERATING CURVE

