

# iQ-LED

## Kanlux

### IQ-LED C37

Světelný zdroj LED



[V] 220-240 AC	[Hz] 50/60	SMD	ellipse ≤ 6x MacAdam	Ra 80	≥40000	(h) 15000
		CE	EAC			



iQ-LED C37E14 5,5W

IQ-LED C37E14 5,5W-WW	<b>27294</b>	5,5	40	470	2700	280	E14 F
IQ-LED C37E14 5,5W-NW	<b>27295</b>	5,5	41	490	4000	280	E14 F
IQ-LED C37E14 5,5W-CW	<b>27296</b>	5,5	41	490	6500	280	E14 F
IQ-LED C37E14 7,5W-WW	<b>27297</b>	7,5	60	810	2700	280	E14 F
IQ-LED C37E14 7,5W-NW	<b>27298</b>	7,5	61	830	4000	280	E14 E
IQ-LED C37E14 7,5W-CW	<b>27299</b>	7,5	61	830	6500	280	E14 E

Kanlux iQ-LED to je fotobiologická bezpečnost, spolehlivost a příznivá barevná teplota pro oči, to vše při zachování klasického designu C37. Žárovky iQ-LED zajišťují naprostý uživatelský komfort a bezpečnost, kterou potvrzuje certifikát TÜV Rheinland.

- Materiál: plast

# iQ-LED

## Kanlux

### IQ-LED C37


Světelný zdroj LED




iQ-LED C37E14 5,5W



iQ-LED C37E14 7,5W



iQ-LED C37E14 5,5W



iQ-LED C37E14 7,5W