

Floodlight without sensor

# LS 150 M

black

EAN 4007841 069216

Article number 069216



LED

30 years (Ø 4,5h / day)

4000 K

4000K neutral white



IP44

3 years

manufacturer's warranty  
steinel.de/garantie



CE



energy saving



plastic free packaging

## Function description

Stylish. Bright: Ideal for courtyards and driveways: The LS 150 M LED floodlight without sensor. Neutral white light (4,000 K), 1760 lm, 22,6 W. Adjustable through 80° horizontally and 150° vertically. The floodlight is switched ON and OFF manually via switch. Protection class IP 44. Colour finish: Black or white.

## Technical specifications

Dimensions (L x W x H)	167 x 157 x 178 mm	Basic light level function	No
Mains power supply	220 – 240 V / 50 – 60 Hz	Main light adjustable	No
Output	22,6 W	Soft light start	No
Interconnection	No	Impact resistance	IK03
Luminous flux	1760 lm	IP-rating	IP44
Colour temperature	4000 K	Protection class	I
Colour variation LED	SDCM3	Ambient temperature	-10 – 30 °C
Farbwiedergabeindex	80-89	Housing material	Aluminium
With lamp	Yes, STEINEL LED system	Manufacturer's Warranty	3 years
Lamp	LED cannot be replaced	Includes corner wall mount	No
LED life expectancy (max. °C)	50000 h	PU1, net weight	0,81 kg
LED cooling system	Passive Thermo Control	Version	black
With motion detector	No	PU1, EAN	4007841069216

## Accessories

EAN 4007841 630560 Corner wall mount LS 150 LED

Floodlight without sensor

# LS 150 M

black

EAN 4007841 069216

Article number 069216



## Dimension Drawing

